

Hydraulikzylinder Zylinder doppelwirkend, ohne Befestigung

alle Angaben in mm

Artikel- nummer	A Kolbenstangen- Ø	B Kolben- Ø	C Außen- Ø	Z Hub/Zylinder- hub	H Kolbenstangen- überstand	E Gesamt- länge	P Druck- anschlüsse BSP	bei 200bar in kg		Gewicht
								Druck- kraft	Zug- kraft	
HYZYDO30-50-100	30	50	60	100	46	270	3/8"	4000	2500	3,60
HYZYDO30-50-200	30	50	60	200	46	370	3/8"	4000	2500	4,90
HYZYDO30-50-300	30	50	60	300	46	470	3/8"	4000	2500	6,20
HYZYDO30-50-400	30	50	60	400	46	570	3/8"	4000	2500	7,50
HYZYDO30-50-500	30	50	60	500	46	670	3/8"	4000	2500	8,80
HYZYDO30-50-600	30	50	60	600	46	770	3/8"	4000	2500	10,10
HYZYDO30-50-700	30	50	60	700	46	870	3/8"	4000	2500	11,40
HYZYDO30-50-800	30	50	60	800	46	970	3/8"	4000	2500	12,70
HYZYDO30-50-900	30	50	60	900	46	1070	3/8"	4000	2500	14,00
HYZYDO30-50-1000	30	50	60	1.000	46	1.170	3/8"	4.000	2.500	15,30
HYZYDO30-50-1100	30	50	60	1.100	46	1.270	3/8"	4.000	2.500	16,60
HYZYDO30-50-1200	30	50	60	1.200	46	1.370	3/8"	4.000	2.500	17,90
HYZYDO30-50-1300	30	50	60	1.300	46	1.470	3/8"	4.000	2.500	19,20
HYZYDO30-50-1400	30	50	60	1.400	46	1.570	3/8"	4.000	2.500	20,50
HYZYDO30-50-1500	30	50	60	1.500	46	1.670	3/8"	4.000	2.500	21,80
HYZYDO30-50-1600	30	50	60	1.600	46	1.770	3/8"	4.000	2.500	23,10
HYZYDO30-50-1800	30	50	60	1.800	46	1.970	3/8"	4.000	2.500	24,40